



Home > Products > ProX Truss > F32 Linear I-Beam Segments 2mm in Black > 9.84 Ft (3.00m) F32 I-Beam Linear Truss Segment | 2mm Wall in BLACK

SKU: XT-F32LB984BLK

Permalink: <http://www.proxdir.com>

[Search on Google](#)

## 9.84 Ft (3.00m) F32 I-Beam Linear Truss Segment | 2mm Wall in BLACK

### Product Images

[Find A Dealer](#)



[Download Product Images](#)

### ProX XT-F32LB984BLK 9.84 Ft (3.00m) F32 I-Beam Linear Truss Segment | 2mm Wall in BLACK

#### Description

The **ProX XT-F32LB984BLK** truss system in 2-point Linear design is particularly well suited for trade shows and shop construction, as well as event technology and as a support system for lighting fixtures. Due to its compact design combined with high load capacity, this system is ideally suited from a simple exhibition stand, up to a complex rig construction project.

ProX Truss has the most trusted staging support systems in the industry and is built to the highest standards of safety and performance. It's a rugged yet lightweight trussing solution perfect for mobile DJs, bands, outdoor performances, nightclubs, live mobile productions, or permanent installations.

At the heart of the system is a square truss that utilizes a standard conical connector system, which easily mates with other brands of truss of the same size and connector style, and is available in a variety of lengths to suit your designs. It also works with different types of corners, base plates, connectors, and accessories that add stability while expanding on limitless configurations.

Always know your load weight for your equipment: **[IMPORTANT - F32 Truss Loading Chart.](#)**

Powder coating provides a stronger finish that is more resistant to damage than paint! Using a black powder coat truss is an effective way to add character to your truss designs. Powder-coated black aluminum ProX truss products provide an extra element that will help to personalize your truss display. Powder-coated finishes provide durability that reduces the risk of scratches, chipping, abrasions, corrosion, fading, and other wear issues.

- **Tolerance Free Standard Conical connector**
- **Main tube wall thickness of .08in (2mm)**



#### XT-F32 SERIES DIMENSIONS:

- Width: 11.42in / 290mm
- Main Tube: 2in / 50mm
- Wall Thickness: .08in / 2mm
- Braces: .75in / 20mm
- Inner Width: 7.5W"
- Brace to Brace: 8.5H"

ProX Truss products utilize industry-standard dimensions to be compatible to connect to/with many other manufacturers trussing.

#### Features

- Download our **Truss Safety Guide**
- **Black Powder Coated**
- **Manufactured in our Own Factory!**
- **Material: EN-AWT6 6082 Aluminum**
- **TUV Certified Aluminium Welding**
- **Includes 1 Set Connecting Hardware**



TUV Is a 3rd Party Certification Body and a Nationally Recognized Testing Laboratory (NRTL). TUV provides inspections, testing, certification & training, with the ultimate objectives of reliability, safety & high quality.

#### Shipping Dimensions & Weight

**Box 1 of 1:** 3.00"H x 12.00"W x 119.00"L - Shipping Weight: 20.00 lbs

**Suggested Shipping Method:** LTL

**UPC**

804589620747

#### Our Products and You

Submit Your Story

#### Customer Testimonials

What Did You  
Think

#### Commonly Asked Questions

Ask A Question

#### Related Products



##### **6.56 Ft. (2.00m) F32 I-Beam Segment Truss 2mm Wall**

SKU: XT-F32-656



##### **4.92 Ft. (1.50m) F32 I-Beam Segment Truss 2mm Wall**

SKU: XT-F32-492



##### **3.28 Ft. (1.00m) F32 I-Beam Vertical or Horizontal Segment Truss 2mm Wall**

SKU: XT-F32-328



---

**7 Degree F32 Truss Corner**

SKU: XT-F32-7D



---

**12 Degree F32 Truss Corner**

SKU: XT-F32-12D



Show  
More